

# 300t MODULAR SPREADER BAR

MAXIRIG PRODUCT CODE  
**MAXIBAR300**

# Maxirig

QUALITY LIFTING SOLUTIONS



## DESCRIPTION

Maximum capacity	300.0 tonne at 60° included sling angle (at 13.0Mtrs span)
Tare weight:	6,600kg Fully Assembled (excl. shackles or rigging gear)
Lifting Lugs (top) suit:	200 tonne Van Beest Sling Saver safety bow shackle
Lifting Lugs (lower) suit:	150 tonne Van Beest Sling Saver safety bow shackle

## PRODUCT ASSURANCE

Parent Standard:	AS4991 - 2004
Proof Load Testing	Yes
MPI Weld Inspection	Yes
Manufacturer's Guarantee	1 Year

LOAD CHART

Span (Mtrs)	WLL (tonnes)		Approx Sling Leg Length (Mtrs)				Approx Headroom (Mtrs)		Modules						
	60°	90°	60°	90°	60°	90°	END LUGS	0.5m	1.0m	2.0m	4.0m	5.0m	5.5m	6.0m	
2.0	300	200	2.0	1.4	1.7	1.0	2								
2.5	300	200	2.5	1.8	2.2	1.3	2	1							
3.0	300	200	3.0	2.1	2.6	1.5	2		1						
3.5	300	200	3.5	2.5	3.0	1.8	2	1	1						
4.0	300	200	4.0	2.8	3.5	2.0	2			1					
4.5	300	200	4.5	3.2	3.9	2.3	2	1		1					
5.0	300	200	5.0	3.5	4.3	2.5	2		1		1				
5.5	300	200	5.5	3.9	4.8	2.8	2	1	1		1				
6.0	300	200	6.0	4.2	5.2	3.0	2				1				
6.5	300	200	6.5	4.6	5.6	3.3	2	1				1			
7.0	300	200	7.0	4.9	6.1	3.5	2		1			1			
7.5	300	200	7.5	5.3	6.5	3.8	2							1	
8.0	300	200	8.0	5.7	6.9	4.1	2	1	1					1	
8.5	300	200	8.5	6.0	7.4	4.3	2		1					1	
9.0	300	200	9.0	6.4	7.8	4.6	2	1						1	
9.5	300	200	9.5	6.7	8.2	4.8	2				1			1	
10.0	300	200	10.0	7.1	8.7	5.1	2	1	1		1			1	
10.5	300	200	10.5	7.4	9.1	5.3	2				1			1	
11.0	300	200	11.0	7.8	9.5	5.6	2					1	1		
11.5	300	200	11.5	8.1	10.0	5.8	2				1			1	1
12.0	300	200	12.0	8.5	10.4	6.1	2				1				
12.5	300	200	12.5	8.8	10.8	6.3	2					1	1	1	1
13.0	300	200	13.0	9.2	11.3	6.6	2					1			1
13.5	250	200	13.5	9.5	11.7	6.8	2							1	1
14.0	250	200	14.0	9.9	12.1	7.1	2	1						1	1
14.5	250	200	14.5	10.3	12.6	7.4	2		1					1	1
15.0	250	200	15.0	10.6	13.0	7.6	2				1			1	1
15.5	250	200	15.5	11.0	13.4	7.9	2				1			1	1
16.0	250	200	16.0	11.3	13.9	8.0	2		1		1			1	1
16.5	250	200	16.5	11.7	14.3	8.3	2		1	1	1			1	1
17.0	250	200	17.0	12.0	14.7	8.5	2				1	1			1
17.5	250	200	17.5	12.4	15.1	8.7	2				1			1	1
18.0	250	200	18.0	12.7	15.6	9.0	2	1			1			1	1
18.5	250	200	18.5	13.0	16.0	9.3	2		1					1	1
19.0	250	200	19.0	13.4	16.5	9.5	2	1				1	1	1	1
19.5	250	200	19.5	13.8	16.9	9.7	2		1			1	1	1	1
20.0	250	200	20.0	14.1	17.3	10.0	2	1	1			1	1	1	1
20.5	250	150	20.5	14.5	17.8	10.2	2				1		1	1	1
21.0	250	150	21.0	14.9	18.2	10.5	2	1			1		1	1	1
21.5	250	150	21.5	15.2	18.6	10.7	2		1		1		1	1	1
22.0	250	150	22.0	15.6	19.1	11.0	2	1	1		1		1	1	1
22.5	200	110	22.5	15.9	19.5	11.2	2				1	1	1	1	1
23.0	200	110	23.0	16.3	19.9	11.5	2	1			1	1	1	1	1
23.5	200	110	23.5	16.6	20.4	11.7	2		1			1	1	1	1
24.0	200	110	24.0	17.0	20.8	12.0	2	1	1		1	1	1	1	1
24.5	150	90	24.5	17.3	21.2	12.2	2				1	1	1	1	1
25.0	150	90	25.0	17.7	21.7	12.5	2	1			1	1	1	1	1
25.5	150	90	25.5	18.0	22.1	12.7	2		1		1	1	1	1	1
26.0	150	90	26.0	18.4	22.5	13.0	2	1	1		1	1	1	1	1

## IMPORTANT

Prior to conducting any operations with this device, a lift study must be undertaken noting the capacity and tare weights of the device in its various configurations.



WE PROVIDE SUPERIOR QUALITY LIFTING PRODUCTS AUSTRALIA WIDE

All Maxirig products are designed and manufactured in Australia by our highly skilled team of engineers and boilermakers.



VISIT [WWW.MAXIRIG.COM.AU](http://WWW.MAXIRIG.COM.AU)