

50t SPREADER BAR END CAP OLD STYLE

Maxirig

QUALITY LIFTING SOLUTIONS



The Maxilug 50 allows users to create their own custom length, medium-lift spreader bar utilizing these heavy duty end units. Designed to accommodate readily available line pipe, Maxirig can supply the units as is or with various pipe lengths to facilitate lift spans from 2 metres up to 12 metres.


MAXIRIG PRODUCT CODE

MAXILUG50 OLD

Capacity:	50 tonne at 60° / 30 tonne at 90°
Tare Weight:	110Kg each / 220Kg per pair (excludes pipe or rigging)
Lifting Lugs (top) suit:	35 tonne Grade 'S' safety bow shackle
Load Lugs (lower) suit:	35 tonne Grade 'S' safety bow shackle
Intermediate Pipe:	273.1mm OD x 6.3mm Wall C350LO (81.6Kg / MTR)

PRODUCT ASSURANCE

Parent Standard:	AS4991 - 2004
Proof Load Testing	Yes
MPI Weld Inspection	Yes
Manufacturer's Guarantee	1 Year



**WE PROVIDE SUPERIOR QUALITY
LIFTING PRODUCTS AUSTRALIA WIDE**

All Maxirig products are designed and manufactured in Australia by our highly skilled team of engineers and boilermakers.



**DYNAMIC
RIGGING HIRE**

VISIT WWW.MAXIRIG.COM.AU