

Dynamic Rigging Hire have the best range of pneumatic chain hoists in Australia and have recently increased the larger capacity range and now stock Ingersoll Rand Liftchain series hoists in 12t and 25t WLL.

Ingersoll Rand are leaders in the pneumatic tool industry dating back to 1924, the heavy duty air hoists have many safety and operating features making them ideal for applications in mining, tunneling, refineries and in general construction.

Reliable

- All steel construction for better durability
- Designed specifically for harsh environments, including resistance to dust and humidity and 100% duty cycle operation
- Grade 80 calibrated load chain resists corrosion
- High-starting torque gear-type air motor offers precise spotting capability
- Variable speed control through pendant with e-stop

Safe

- Spark resistant design ideal for potentially explosive atmosphere; classified as an equipment category 3 per ATEX Directive 2014/34/EU for zone 2 of Directive 1999/92/EC
- Reduced maintenance, self-adjusting automatic disc brake fully enclosed for better protection
- CE-certified models include overload protection, emergency stop and built-in main air shut-off valve

Versatile

- Numerous application-specific options available, including chain containers (fabric or metallic) and rigid mounting trolleys (plain, geared or motorized)
- Low maintenance, self-adjusting automatic disc brake fully enclosed for better protection
- Upper and lower limit switch allows hoist to be used in a horizontal position



Model	WLL	Height of lift available	Falls of chain	Motor (HP)	Lifting speed at rated load (m/min)	Air cons. At rated load (m ³ /min)	Air inlet size (BSP)**	Sound (dba)	Hoist weight as standard 3m HOL	Chain size	Chain weight kg/m
LC2A12ODI	12t	3, 7, 15 & 22m	2	6	1.3	5	1"	79	277kg	16x45	5.7
LC2A25OQI	25t	3, 5, 7 & 10m	4	6	0.9	5	1"	79	324kg	16x45	5.7

Hoist height of lift (or chain fall) can be supplied to suit your requirements subject to length of chain availability, please allow an additional day lead time to prepare and test. Weight of hoist shall increase with longer chain falls.

**Note hoists air hose fitting supplied is Minsup A type and may only be changed with authority

**Australia's Best
Range of Quality
Heavy Rigging Gear**

CALL 03 8360 8910

email sales@dynamicrigging.com.au

website dynamicrigginghire.com.au

96 North View Drive Sunshine West Vic. 3020