

SwiftLiftTM Lifting Clutch

SwiftLift Lifting Clutches cover the full SwiftLift range from 1.3t to 32t WLL.

SwiftLift Clutches have been designed so that they cannot spontaneously disengage whilst the system is under load at any orientation, provided they are correctly connected to the head of the correct anchor in the recess. When the lift is complete and the load released, the SwiftLift Clutch is quickly and simply disengaged.

Part No.	Pack Qty	WLL (Max)
1LE	1	1.3t
2LE	1	2.5t
5LE	1	5.0t
10LE	1	10.0t
20LE	1	20.0t
32LE	1	32.0t



SwiftLift Lifting Clutch markings



WLL per clause 2.6 (iii)



Reid batch number
(on underside)



Reid name & symbol
per clause 2.6



Unique identifying serial
number per clause 2.6 (i)



Reid name & symbol
per clause 2.6 (ii)
(on side of sphere)



As per AS 3850.1:2015 clause 2.6, all clutches need to be permanently marked with a unique identifier (traceable to proof tests), the manufacturers symbol or name, and the WLL or compatible anchor identified. All Reid SwiftLift Lifting Clutches comply with this clause.

Note: Clutch markings shown are typical of 1, 2 & 5t clutches. Markings on AS 3850.1:2015 compliant 10, 20 and 32t clutches may vary from that shown here.